

REPORT NUMBER 114-GTL-09-008

SAFETY COMPLIANCE TESTING FOR FMVSS NO. 114 THEFT PROTECTION

MAZDA MOTOR CORPORATION
2009 MAZDA 3, PASSENGER CAR
NHTSA NO. C95400

GENERAL TESTING LABORATORIES, INC.
1623 LEEDSTOWN ROAD
COLONIAL BEACH, VIRGINIA 22443



July 20, 2009

FINAL REPORT

PREPARED FOR

**U. S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
ENFORCEMENT
OFFICE OF VEHICLE SAFETY COMPLIANCE
1200 NEW JERSEY AVE., SE
WASHINGTON, D.C. 20590**

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned, it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared By: _____

Approved By: _____

Approval Date: 07/20/09

FINAL REPORT ACCEPTANCE BY OVSC:

Accepted By: 

Acceptance Date: 7/20/09

1. Report No. 114-GTL-09-008	2. Government Accession No. N/A	3. Recipient's Catalog No. N/A
4. Title and Subtitle Final Report of FMVSS 114 Compliance Testing of a 2009 MAZDA 3 PASSENGER CAR NHTSA No. C95400		5. Report Date July 20, 2009
		6. Performing Organ. Code GTL
7. Author(s) Grant Farrand, Project Engineer Debbie Messick, Project Manager		8. Performing Organ. Rep# GTL-DOT-09-114-008
9. Performing Organization Name and Address General Testing Laboratories, Inc. 1623 Leedstown Road Colonial Beach, Va 22443		10. Work Unit No. (TRAIS) N/A
		11. Contract or Grant No. DTNH22-06-C-00032
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Admin. Enforcement Office of Vehicle Safety Compliance (NVS-220) 1200 New Jersey Ave., S.E., Washington, DC 20590		13. Type of Report and Period Covered Final Test Report June 11, 2009
		14. Sponsoring Agency Code NVS-221
15. Supplementary Notes		
16. Abstract Compliance tests were conducted on the subject 2009 Mazda 3 4-door passenger car in accordance with the specifications of the Office of Vehicle Safety Compliance Test Procedure No. TP-114-03-DRAFT-GTL-REVC for the determination of FMVSS 114 compliance. Test failures identified were as follows: None		
17. Key Words Compliance Testing Safety Engineering FMVSS 114		18. Distribution Statement Copies of this report are available from NHTSA Technical Information Services (TIS) Room W45-212 (NPO-411) 1200 New Jersey Ave., S.E. Washington, DC 20590 Telephone No. (202) 366-4947
19. Security Classif. (of this report) UNCLASSIFIED	21. No. of Pages 25	22. Price
20. Security Classif. (of this page) UNCLASSIFIED		

TABLE OF CONTENTS

SECTION	PAGE
1. Purpose of Compliance Test	1
2. Test Procedure and Summary of Results	2
3. Test Data	3
4. Test Equipment List	13
5. Photographs	14
5.1 ¾ Frontal View from Left Side of Vehicle	
5.2 Vehicle Certification Label	
5.3 Vehicle Tire Information Label	
5.4 Close-up View of Ignition Key	
5.5 Starting System Control	
5.6 Transmission Gear Selection Control	
5.7 Device which allows moving Gear Selector out of Park Position	

SECTION 1

PURPOSE OF COMPLIANCE TEST

1.0 PURPOSE OF TEST

A model year 2009 Mazda 3 passenger car was subjected to Federal Motor Vehicle Safety Standard (FMVSS) No. 114 testing to determine if the vehicle was in compliance with the requirements of the standard. FMVSS 114 specifies requirements to decrease the likelihood that a vehicle is stolen, or accidentally set in motion.

1.1 The test vehicle was a 2009 Mazda 3 Passenger Car. The vehicle was identified as follows:

A. Vehicle Identification Number: JM1BK323691232072

B. NHTSA No.: C95400

C. Manufacturer: MAZDA MOTOR CORPORATION

D. Manufacture Date: 09/08

E. Color: Sunlight Silver Metallic

1.2 TEST DATE

The test vehicle was subjected to FMVSS No. 114 testing on June 11, 2009.

SECTION 2

TEST PROCEDURE AND SUMMARY OF RESULTS

2.0 TEST PROCEDURE

All tests were conducted in accordance with NHTSA, Office of Vehicle Safety Compliance (OVSC) Laboratory Procedure TP-114-03-DRAFT-GTL-REVC and General Testing Laboratories, Inc. (GTL) Test Procedure, TP-114-03-Draft, "Theft Protection and Rollaway Prevention".

2.1 SUMMARY OF RESULTS

Test data indicate the FMVSS 114 requirements appear to have been satisfied. All test data resulting from the tests were recorded on test data sheets in Section 3.

SECTION 3

TEST DATA

3.0 TEST RESULTS

The following data sheets document the results of FMVSS 114 testing on the 2009 Mazda 3.

FMVSS 114, THEFT PROTECTION
DATA SHEET 1 continued

GEAR SELECTION CONTROL

Describe the gear selection control:

Center Console mounted Gear Shift Lever

Describe how the gear selection control is activated:

Press and hold brake while moving gear selector to desired position

Describe all of the selectable settings:

Park, Reverse, Neutral, Drive, Manual

IMMOBILIZER

Is the vehicle equipped with an immobilizer YES NO

Describe the immobilizer device and how it prevents vehicle theft (if equipped):

Code embedded in key. Engine will not start with an unrecognized key

OPTIONAL RELEASE DEVICES

Describe if the vehicle is equipped with optional release devices:

Yes for shifter

OPTIONAL RELEASE DEVICES:

Key Removal Gear Selection Control None Other

VEHICLE FLUIDS

Check all vehicle fluids and adjust to the proper levels for operation: Full

VEHICLE TIRE PLACARD INFORMATION

Vehicle Mfg. Recommended Tire Inflation Pressure

(kPa): Front 220 Rear 220


TIRE INFLATION PRESSURES:

Measured (kPa): LF 220 LR 220 RF 220 RR 220

WEIGHT

Vehicle Curb Weight(kg): 1348 Weight of Driver (kg): 91 (target = 91kg)

FMVSS 114, THEFT PROTECTION
DATA SHEET 2

REQUIREMENT S5.1.1	PASS	FAIL
Engine cannot be started without using the key <u> X </u> Yes <u> </u> No	X	
<p>With key removed, steering wheel locks: Yes: <u> X </u> No: <u> </u></p> <p>Identify locking position(s) on wheel using arrow(s)</p> <p>Clockwise: <u> 8 </u> (degrees) Counterclockwise: <u> 15 </u> (degrees)</p> <div style="text-align: right; margin-top: 10px;">  </div>		
<p>Key removal prevents forward self-mobility: Yes: <u> X </u> No: <u> </u></p> <p>If yes describe: Vehicle will not start without key in vehicle and the steering locks.</p>		
When key is removed from the starting system, starting of the engine or motor and either steering or self mobility is prevented. YES	X	

REMARKS:

FMVSS 114, THEFT PROTECTION
DATA SHEET 2 continued

REQUIREMENT S5.1.3	PASS	FAIL
<p>An audible warning is activated whenever the key is in any starting system position with the exception of "on" and "start" and the door closest to the driver's designated seating position is opened.</p> <p align="right">Yes <u> X </u> No _____</p> <p>Identify ALL key/starting system position setting: <u>Lock, Accessory, On/Run, Start</u></p>	X	

REQUIREMENT S5.1.4	PASS	FAIL
<p>With the vehicle engine or motor shut down and the transmission gear selection control in any position other than "park";</p> <p>The steering wheel can rotate without locking? Yes <u> X </u> No _____</p>	X	
<p>The vehicle is free to roll forward? Yes <u> X </u> No _____</p>	X	

REMARKS:

RECORDED BY: G. Farrand
APPROVED BY: D. Messick

DATE: 06/11/09

FMVSS 114, ROLLAWAY PREVENTION
DATA SHEET 3
(for vehicles equipped with transmission with a "park" position)

VEH. NHTSA NO.: C95400

TEST DATE: 06/11/09

REQUIREMENT S5.2.1	PASS	FAIL
<p>The starting system prevents key removal in ALL gear selection control positions except "park". Yes <u> X </u> No <u> </u></p> <p>Can the gear selection control be placed between each gear selection position and will it remain there without assistance? Yes <u> </u> No <u> X </u></p> <p>If yes, can the key be removed from the starting system? Yes <u> </u> No <u> </u></p> <p>If the key can be removed from the vehicle starting system when the gear selection control is not locked in "park", a mechanism shall exist which, upon key removal, the vehicle transmission or gear selection control shall become locked in "park" as the direct result of removing the key. If such a mechanism exists, describe the mechanism and its function:</p>	X	

REQUIREMENT S5.2.2	PASS	FAIL
<p>The gear selection control is locked in the "park" position when the key is removed from the starting system. Yes <u> X </u> No <u> </u></p>	X	

REMARKS:

DATA SHEET 3 continued

REQUIREMENT S5.2.3	PASS	FAIL
<p><u>ELECTRICAL FAILURE (Battery Discharge)</u></p> <p>In the event of an electrical failure, key removal from the starting system when the transmission or gear selection control is not locked in “park” is permitted”. Yes_____ No <u>X</u></p> <p>The vehicle is equipped with an override device that permits key removal from the starting system when the transmission or gear selection control is not locked in “park”. Yes_____ No <u>X</u></p> <p>If yes, select the type of override device equipped: Opaque Cover_____ No Cover_____</p> <p>Describe the override device design and mode of activation (if equipped):</p>	X	
	X	
	N/A	
<p>FILL IN THE SECTION BELOW THAT APPLIES:</p> <p><u>OVERRIDE WITH AN OPAQUE COVER:</u></p> <p>The opaque surface cover prevents sight of and use of override device. Yes_____ No_____</p> <p>The opaque surface cover can only be removed by using a screwdriver or other tool. Yes_____ No_____</p> <p>As a direct result of removing the key from starting system, the following is prevented: Steering_____ or Self-Mobility_____</p> <p><u>OVERRIDE WITH NO COVER</u></p> <p>The override device requires the use of a tool to activate. Yes_____ No_____</p> <p>Simultaneous activation of the override device and removal of key from starting system is required. Yes_____ No_____</p> <p>As a direct result of removing the key from the starting system, the following is prevented: Steering_____ or Self-Mobility_____</p>	N/A	

REMARKS:

DATA SHEET 3 continued

REQUIREMENT S5.2.4	PASS	FAIL
<p><u>GEAR SELECTION CONTROL OVERRIDE DEVICE</u></p> <p>The vehicle is equipped with an override device that allows the user to move the gear selection control from “park” after the key has been removed from the starting system. Yes <u>X</u> No _____</p> <p>If yes, select the type of override device that is equipped: Override operated with a: Key _____ Opaque Cover <u>X</u> No Cover _____</p> <p>Describe the override device design and mode of activation (if equipped): Remove cover on shifter housing and insert screwdriver and push down</p> <p>FILL IN THE SECTION BELOW THAT APPLIES:</p> <p><u>VERRIDE OPERATED WITH KEY:</u></p> <p>The key is required to operate the override device that allows the user to move the gear selection control from “park” after the key has been removed from the starting system. Yes _____ No _____</p> <p><u>VERRIDE WITH AN OPAQUE COVER</u></p> <p>The opaque surface cover prevents sight of and use of override device. Yes <u>X</u> No _____</p> <p>The opaque surface cover can only be removed by using a screwdriver or other tool. Yes <u>X</u> No _____</p> <p>As a direct result of removing the key from the starting system, the following is prevented: Steering <u>X</u> or Self-Mobility _____</p> <p><u>VERRIDE WITH NO COVER</u></p> <p>The override device requires the use of a tool to operate. Yes _____ No _____</p> <p>Simultaneous activation of the override device and removal of key from starting system is required. Yes _____ No _____</p> <p>As a direct result of removing the key from the starting system, the following is prevented: Steering _____ or Self-Mobility _____</p>	<p>X</p> <p>N/A</p> <p>X</p> <p>N/A</p>	

REMARKS:

DATA SHEET 3 continued

REQUIREMENTS S5.3	PASS	FAIL
<u>VEHICLE FACING UPHILL ON 10% GRADE</u>		
With the key in the "off" position, the transmission will shift out of "park" without the service brake being applied. Yes_____ No <u>X</u>	<u>X</u>	
With the key in the "acc" position, the transmission will shift out of "park" without the service brake being applied. Yes_____ No <u>X</u>	<u>X</u>	
With the key in the "on" position (engine off), the transmission will shift out of "park" without the service brake being applied. Yes_____ No <u>X</u>	<u>X</u>	
With the key in the "start" position, the transmission will shift out of "park" without the service brake being applied. Yes_____ No <u>X</u>	<u>X</u>	
With the key in the "other" position (please specify), the transmission will shift out of "park" without the service brake being applied. Yes_____ No <u>X</u>	<u>X</u>	
Does the key stay between starting system positions without being held by operator? Yes_____ No <u>X</u> If so, please describe.	<u>X</u>	
Brake force readings (force required to allow the transmission to shift out of "park"):		
The vehicle is equipped with adjustable pedals: Yes_____ No <u>X</u>		
Fore Position:		
Reading 1 <u>23.1 N</u>		
Reading 2 <u>24.4 N</u>		
Reading 3 <u>22.2 N</u>		
Reading 4 <u>22.2 N</u>		
Reading 5 <u>22.7 N</u> Avg. <u>22.9 N</u>	<u>X</u>	

REMARKS:

RECORDED BY: G. FarrandDATE: 06/11/09APPROVED BY: D. Messick

SECTION 4
TEST EQUIPMENT LIST

ITEM	MFR	MODEL	S/N	CAL. PERIOD	DATE OF NEXT CALIB.	REMARKS
SLR DIGITAL CAMERA	NIKON	D50	N/A	N/A	N/A	
TIRE PRESSURE GAUGE	WESKLER	45-0/100	107	12 MO.	03/10	
INCLINOMETER	MITUTOYO	PRO 360	950-315	N/A	BEFORE USE	
STEEL TAPE	STANLEY	FAT MAX	33-890	12 MO.	03/10	
WHEEL SCALES	INTERCOMP	SERIES 94	199744	12 MO.	04/10	
WHEEL SCALES	INTERCOMP	SERIES 94	199744	12 MO.	04/10	
WHEEL SCALES	INTERCOMP	SERIES 94	199744	12 MO.	04/10	
WHEEL SCALES	INTERCOMP	SERIES 94	199744	12 MO.	04/10	
SPRING SCALE	CHATILLON	DPP-10	4729	12 MO.	04/10	

SECTION 5
PHOTOGRAPHS



2009 MAZDA 3
NHTSA NO. C95400
FMVSS NO. 114

FIGURE 5.1
¾ FRONTAL VIEW FROM LEFT SIDE OF VEHICLE

MFD. BY MAZDA MOTOR CORPORATION

DATE	GVWR/PNBV	GAWR/PNBE FRT	GAWR/PNBE RR
09/08	3951 LB 1792 KG	2163 LB 981 KG	1788 LB 811 KG

THIS VEHICLE CONFORMS TO ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY
/ BUMPER, AND THEFT PREVENTION
STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

JM1BK323691232072

TYPE: PASSENGER




BODY COLOR CODE; 22V

MADE IN JAPAN

2009 MAZDA 3
NHTSA NO. C95400
FMVSS NO. 114

FIGURE 5.2
VEHICLE CERTIFICATION LABEL



TIRE AND LOADING INFORMATION

SEATING CAPACITY : TOTAL 5 : FRONT 2 : REAR 3

The combined weight of occupants and cargo should never exceed 385kg or 850lbs.

TIRE	SIZE	COLD TIRE PRESSURE
FRONT	P205/50R17	220KPA, 32PSI
REAR	P205/50R17	220KPA, 32PSI
SPARE	T125/70D16	420KPA, 60PSI

SEE OWNER'S
MANUAL FOR
ADDITIONAL
INFORMATION

(BAP1A)

FIGURE 5.3
VEHICLE TIRE INFORMATION LABEL



2009 MAZDA 3
NHTSA NO. C95400
FMVSS NO. 114

FIGURE 5.4
CLOSE-UP VIEW OF IGNITION KEY



2009 MAZDA 3
NHTSA NO. C95400
FMVSS NO. 114

FIGURE 5.5
STARTING SYSTEM CONTROL



2009 MAZDA 3
NHTSA NO. C95400
FMVSS NO. 114

FIGURE 5.6
TRANSMISSION GEAR SELECTION CONTROL



2009 MAZDA 3
NHTSA NO. C95400
FMVSS NO. 114

FIGURE 5.7
DEVICE WHICH ALLOWS MOVING GEAR SELECTOR OUT OF
PARK POSITION