

REPORT NUMBER: 301-MGA-2011-007

**SAFETY COMPLIANCE TESTING FOR FMVSS 301R
FUEL SYSTEM INTEGRITY – REAR IMPACT**

**KIA MOTORS MANUFACTURING
2011 KIA SORENTO
NHTSA NUMBER: CB0507**

**PREPARED BY:
MGA RESEARCH CORPORATION
5000 WARREN ROAD
BURLINGTON, WI 53105**



Test Date: August 17, 2011


Final Report Date: September 8, 2011

FINAL REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
ENFORCEMENT
OFFICE OF VEHICLE SAFETY COMPLIANCE
1200 NEW JERSEY AVENUE, S.E., NVS-220
WASHINGTON, D.C. 20590**

This final test report was prepared for the U.S. Department of Transportation, National Highway Traffic Safety Administration, in response to Contract Number DTNH22-06-C-00030.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared by: 
Joe Fleck, Project Engineer

Date: August 24, 2011

Reviewed by: 
David Winkelbauer, Facility Director

Date: August 24, 2011

FINAL REPORT ACCEPTED BY:

Edward E. Chan

Digitally signed by Edward E. Chan
DN: cn=Edward E. Chan, o=National Highway Traffic Safety
Administration, ou=Office of Vehicle Safety Compliance,
email=ed.chan@dot.gov, c=US
Date: 2011.09.08 13:40:13 -04'00'

COTR, Rear Impact

9/8/2011

Date of Acceptance

Technical Report Documentation Page

1. Report No. 301-MGA-2011-007		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle Final Report for Fuel System Integrity Test of a 2011 KIA Sorento NHTSA No.: CB0507				5. Report Date August 24, 2011	
				6. Performing Organization Code MGA	
7. Author(s) Joe Fleck, Project Engineer				8. Performing Organization Report No. 301-MGA-2011-007	
9. Performing Organization Name and Address MGA Research Corporation 5000 Warren Road Burlington, WI 53105				10. Work Unit No.	
				11. Contract or Grant No. DTNH22-06-C-00030	
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Enforcement, Office of Vehicle Safety Compliance 1200 New Jersey Avenue, S.E., NVS-220 Washington, D.C. 20590				13. Type of Report and Period Covered Final Report August 17, 2011 – September 8, 2011	
				14. Sponsoring Agency Code NVS-220	
15. Supplementary Notes					
16. Abstract A rear impact was conducted on a 2011 KIA Sorento at MGA Research Corporation on August 17, 2011. This test was conducted to obtain data indicant of FMVSS 301R. The impact velocity was 79.3 km/h. The ambient temperature at the time of impact was 27 degrees Celsius.					
17. Key Words Fuel System Integrity Test 2011 KIA Sorento NHTSA No: CB0507				18. Distribution Statement Copies of this report are available from: National Highway Traffic Safety Admin., Technical Ref. Division, 1200 New Jersey Avenue, SE Washington, D.C. 20590	
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of Pages 57	22. Price

TABLE OF CONTENTS

<u>Section</u>		<u>Page No</u>
1	Purpose and Summary of Test	1
2	Data Sheets	2

<u>Data Sheet No.</u>		<u>Page No.</u>
1	Test Vehicle Specifications	2
2	Pre-Test Data	4
3	Moving Barrier Data	6
4	Post-Test Data	7
5	Static Rollover Test Data	8

<u>Form No.</u>		
1	Test Vehicle Information	10

<u>Appendix</u>		
A	Photographs	A

SECTION 1

PURPOSE AND SUMMARY OF TEST

PURPOSE

This rear impact test is sponsored by the National Highway Traffic Safety Administration (NHTSA) under contract number DTNH22-06-C-00030. The purpose of this test is to reduce deaths and injuries occurring from fires that result from fuel spillage during and after motor vehicle crashes and resulting from ingestion of fuels during siphoning.

SUMMARY

A 2011 KIA Sorento was impacted by a Moving Deformable Barrier (MDB) at a velocity of 79.3 km/h. The test was performed at MGA Research Corporation on August 17, 2011. Pre-and post-test photographs of the vehicle and dummies can be found in Appendix A.

One real-time camera and five high-speed cameras were used to document the impact event.

- Left Rear Half 1000 fps
- Right Rear Half 1000 fps
- Overhead Overall 1000 fps
- Left Overall 1000 fps
- Right Overall 1000 fps
- Real Time Pan 30 fps

Two ballast Part 572E, 50th percentile male anthropomorphic test devices (ATDs) were placed in the driver and right-front passenger seating positions according to dummy placement instructions specified in the Laboratory Indicant Test Procedure.

There was no Stoddard Solvent leakage after the event or during any phase of the static rollover.

The vehicle appeared to comply with all the requirements of FMVSS No. 301 "Fuel System Integrity."

**SECTION 2
DATA SHEETS**

**DATA SHEET NO. 1
TEST VEHICLE SPECIFICATIONS**

Test Vehicle: 2011 KIA Sorento NHTSA No.: CB0507
 Test Program: FMVSS 301 Fuel System Integrity Test Date: 8/17/2011

TEST VEHICLE INFORMATION

Manufacturer	KIA Motors Manufacturing Georgia, Inc.
Model	Sorento
Body Style	SUV
Major Options	None
NHTSA No.	CB0507
VIN	5XYKT3A12BG147653
Color	Bright Silver
Delivery Date	7/26/2011
Odometer Reading (mile)	182
Dealer	Dorsch Kia
Transmission	Manual
Final Drive	Front Wheel Drive
Number of Cylinders	4
Engine Displacement (L)	2.4
Engine Placement	Lateral

DATA FROM VEHICLE'S CERTIFICATION LABEL

Manufactured By	KIA Motor Manufacturing Georgia, Inc.
Date of Manufacture	1/24/11

GVWR (kg)	2190
GAWR Front (kg)	1350
GAWR Rear (kg)	1450

VEHICLE CAPACITY DATA

Measured Parameter	Front	Rear	Third	Total
Type of Seats	Bucket	Bench		
Number of Occupants	2	3		5
Capacity Wt. (VCW) (kg)				420
Number of Occupants x 68 kg.				340
Cargo Wt. (RCLW) (kg)				80

DATA SHEET NO. 1 (continued)
TEST VEHICLE SPECIFICATIONS

Test Vehicle: 2011 KIA Sorento NHTSA No.: CB0507
 Test Program: FMVSS 301 Fuel System Integrity Test Date: 8/17/2011

DATA FROM VEHICLE'S TIRE PLACARD

Measured Parameter	Front	Rear
Maximum Tire Pressure (kPa)	300	300
Cold Pressure (kPa)	230	230
Recommended Tire Size	P235/65R17	P235/65R17
Recommended Load Range	103T	103T
Tire Size on Vehicle	P235/65R17	P235/65R17
Tire Manufacturer	Kumho	Kumho
Location of Placard of Vehicle	Lower B-Post	
Type of Spare Tire (full size/space saver)	Space Saver	

DATA SHEET NO. 2

PRE-TEST DATA

Test Vehicle: 2011 KIA Sorento

NHTSA No.: CB0507

Test Program: FMVSS 301 Fuel System Integrity

Test Date: 8/17/2011

WEIGHT OF TEST VEHICLE

	Units	As Delivered (UVW) (Axle)			As Tested (ATW) (Axle)		
		Front	Rear	Total	Front	Rear	Total
Left	kg	469.0	359.7		520.3	429.1	
Right	kg	470.8	344.3		510.8	406.9	
Ratio	%	57.2	42.8		55.2	44.8	
Totals	kg	939.8	704.0	1643.8	1031.1	836.0	1867.1

CALCULATION OF TARGET TEST WEIGHT (TTW)

Measured Parameter	Units	Value
Total Delivered Weight (UVW)	kg	1643.8
Rated Cargo/Luggage Weight (RCLW)	kg	80
Weight of 2 P572E ATDs	kg	148
Calculated Vehicle Target Weight (TVTW)	kg	1871.8

Vehicle Wheelbase	2704 mm
Vehicle Width	1880 mm
Weight of Ballast Secured in Rear Seat	78.9 kg
Method of Securing Ballast	Ratchet Straps
Vehicle Components Removed for Weight Reduction	None

VEHICLE ATTITUDES

	Units	LF	RF	LR	RR
As Delivered	mm	805	801	800	803
As Tested	mm	793	791	780	784

DATA SHEET NO. 2 (continued)

PRE-TEST DATA

Test Vehicle: 2011 KIA Sorento NHTSA No.: CB0507
 Test Program: FMVSS 301 Fuel System Integrity Test Date: 8/17/2011

FUEL SYSTEM DATA

	Units: Liters
Usable Capacity of "Standard Tank" (Owner's Manual)	68.0
Usable Capacity Figure Furnished by COTR	68.0
Usable Capacity of "Optional" Tank	
92-94% of Usable Capacity	62.5 to 63.9
Actual Test Volume (entire fuel system filled)	63.2

Test Fluid Type	Stoddard Solvent
Test Fluid Kinematic Viscosity (centistokes)	2.1 cSt @ 20° C
Test Fluid Color	Purple
Type of Vehicle Fuel Pump	Electrical
Activate Electric Fuel Pump Operation with Ignition Switch ON, but Engine OFF	Yes

Comments (noticeable attributes of fuel system components, capacity, etc.)	None
--	------

DATA SHEET NO. 3
MOVING BARRIER DATA

Test Vehicle: 2011 KIA Sorento NHTSA No.: CB0507
 Test Program: FMVSS 301 Fuel System Integrity Test Date: 8/17/2011

MOVING BARRIER'S TEST WEIGHT

	Units	Front	Rear	Total
Left	kg	401.4	279.6	
Right	kg	368.9	312.5	
Ratio	%	56.5	43.5	
Totals	kg	770.3	592.1	1362.4

Tires (Mfr, line, size)	Kumho
Tire Pressure (kPa)	220
Brake Abort System (Yes/No)?	Yes
Date of Last Calibration	6/24/11

DATA SHEET NO. 4

POST-TEST DATA

Test Vehicle: 2011 KIA Sorento NHTSA No.: CB0507
Test Program: FMVSS 301 Fuel System Integrity Test Date: 8/17/2011

IMPACT VELOCITY

	Units: km/h
Required Impact Velocity	80.0
Actual Impact Velocity (Trap No. 1)	79.3
Actual Impact Velocity (Trap No. 2)	79.3
Average Impact Speed	79.3

Temperature at Time of Impact (°C)	27
Test Time	11:42 am

WELDING ROD IMPACT POINT

	Units: mm
Vertical distance from target center (+ above target / - below target)	13 up
Horizontal distance from target center (+ to the right / - to the left)	3 left


**DATA SHEET NO. 5
STATIC ROLLOVER TEST DATA**

Test Vehicle: 2011 KIA Sorento NHTSA No.: CB0507
 Test Program: FMVSS 301 Fuel System Integrity Test Date: 8/17/2011

STODDARD SOLVENT SPILLAGE MEASUREMENT

- A. From impact until vehicle motion ceases: 0 g
 (Maximum Allowable = 28 grams)
- B. For the 5 minute period after motion ceases: 0 g
 (Maximum Allowable = 28 grams)
- C. For the following 25 minutes: 0 g
 (Maximum Allowable = 28 grams/minute)
- D. Spillage: None

FMVSS 301 STATIC ROLLOVER DATA



1. The specified fixture rollover rate for each 90° of rotation is 60 to 180 seconds.

2. The position hold time at each position is 300 seconds (minimum).

3. Details of Stoddard Solvent spillage locations: **Not Applicable**

DATA SHEET NO. 5 (continued)
STATIC ROLLOVER TEST DATA

Test Vehicle: 2011 KIA Sorento NHTSA No.: CB0507
 Test Program: FMVSS 301 Fuel System Integrity Test Date: 8/17/2011

STODDARD SOLVENT SPILLAGE MEASUREMENT
Hold Time = 5 minutes at all intervals

0° TO 90° Rotation Time (sec) = 116 sec

Test Phase	Spillage (g)	Spillage Details
First 5 minutes from onset of rotation	0	
Sixth minute from onset of rotation	0	
Seventh minute from onset of rotation	0	
Eight minute if required	N/A	

90° TO 180° Rotation Time (sec) = 114 sec

Test Phase	Spillage (g)	Spillage Details
First 5 minutes from onset of rotation	0	
Sixth minute from onset of rotation	0	
Seventh minute from onset of rotation	0	
Eight minute if required	N/A	

180° TO 270° Rotation Time (sec) = 109 sec

Test Phase	Spillage (g)	Spillage Details
First 5 minutes from onset of rotation	0	
Sixth minute from onset of rotation	0	
Seventh minute from onset of rotation	0	
Eight minute if required	N/A	

270° TO 360° Rotation Time (sec) = 113 sec

Test Phase	Spillage (g)	Spillage Details
First 5 minutes from onset of rotation	0	
Sixth minute from onset of rotation	0	
Seventh minute from onset of rotation	0	
Eight minute if required	N/A	


FORM 1
TEST VEHICLE INFORMATION

Test Vehicle: 2011 KIA Sorento
Test Program: FMVSS 301 Fuel System Integrity

NHTSA No.: CB0507
Test Date: 8/17/2011

NORMAL DESIGN RIDING POSITION

With the seat in the mid fore-aft seat track position the angle of the driver's seat back when it is in the nominal riding position is set at a headrest post angle of -0.7 degrees. Front outboard passenger seat is set at 0.2 degrees, reference to front door sill.



Driver Seat Back Angle	-0.2°
Passenger Seat Back Angle	-1.0°

SEAT FORE/AFT POSITIONING

	Total Fore/Aft Travel	Placed in Position #
Driver Seat	24 detents	11 th detent forward most, 1 st as 0
Passenger Seat	22 detents	11 th detent forward most, 1 st as 0

D-RING ADJUSTMENT

The driver and passenger D-rings were full up.

STEERING COLUMN ADJUSTMENT

The steering column was placed in the mid position.

APPENDIX A
PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

Page No.

Photo No. 1.	Vehicle's Certification Label	A-1
Photo No. 2.	Vehicle's Tire Placard	A-2
Photo No. 3.	Pre-Test Front View of Vehicle	A-3
Photo No. 4.	Post-Test Front View of Vehicle	A-4
Photo No. 5.	Pre-Test Left Side View of Vehicle	A-5
Photo No. 6.	Post-Test Left Side View of Vehicle	A-6
Photo No. 7.	Pre-Test Left Rear Close-up View of Vehicle	A-7
Photo No. 8.	Post-Test Left Rear Close-up View of Vehicle	A-8
Photo No. 9.	Pre-Test Right Side View of Vehicle	A-9
Photo No. 10.	Post-Test Right Side View of Vehicle	A-10
Photo No. 11.	Pre-Test Right Rear Close-up View of Vehicle	A-11
Photo No. 12.	Post-Test Right Rear Close-up View of Vehicle	A-12
Photo No. 13.	Pre-Test Rear View of Vehicle	A-13
Photo No. 14.	Post-Test Rear View of Vehicle	A-14
Photo No. 15.	Pre-Test $\frac{3}{4}$ Frontal View From Right Side of Vehicle	A-15
Photo No. 16.	Post-Test $\frac{3}{4}$ Frontal View From Right Side of Vehicle	A-16
Photo No. 17.	Pre-Test $\frac{3}{4}$ Rear View From Right Side of Vehicle	A-17
Photo No. 18.	Post-Test $\frac{3}{4}$ Rear View From Right Side of Vehicle	A-18
Photo No. 19.	Pre-Test $\frac{3}{4}$ Rear View From Left Side of Vehicle	A-19
Photo No. 20.	Post-Test $\frac{3}{4}$ Rear View From Left Side of Vehicle	A-20
Photo No. 21.	Pre-Test Impact Point	A-21
Photo No. 22.	Post-Test Impact Point	A-22
Photo No. 23.	Pre-Test Underbody View 1	A-23
Photo No. 24.	Post-Test Underbody View 1	A-24
Photo No. 25.	Pre-Test Underbody View 2	A-25
Photo No. 26.	Post-Test Underbody View 2	A-26
Photo No. 27.	Pre-Test Underbody View 3	A-27

Page No.

Photo No. 28.	Post-Test Underbody View 3	A-28
Photo No. 29.	Pre-Test Front View of MDB	A-29
Photo No. 30.	Post-Test Front View of MDB	A-30
Photo No. 31.	Pre-Test $\frac{3}{4}$ Right Side View of MDB	A-31
Photo No. 32.	Post-Test $\frac{3}{4}$ Right Side View of MDB	A-32
Photo No. 33.	Pre-Test $\frac{3}{4}$ Left Side View of MDB	A-33
Photo No. 34.	Post-Test $\frac{3}{4}$ Left Side View of MDB	A-34
Photo No. 35.	Pre-Test Top View of MDB	A-35
Photo No. 36.	Post-Test Top View of MDB	A-36
Photo No. 37.	Static Rollover at 90 Degrees	A-37
Photo No. 38.	Static Rollover at 180 Degrees	A-38
Photo No. 39.	Static Rollover at 270 Degrees	A-39
Photo No. 40.	Static Rollover at 360 Degrees	A-40



MANUFACTURED BY

KIA MOTORS MANUFACTURING GEORGIA, INC.

JAN/24/11

GVWR 4828 lbs PAINT 3D

TRIM H9

GAWR

TIRES

RIMS

COLD TIRE INFL

FRONT 2977 lbs

P235/65R17

7.0JX17

33psi SINGLE

REAR 3197 lbs

P235/65R17

7.0JX17

33psi SINGLE

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.A. FEDERAL
MOTOR VEHICLE SAFETY AND THEFT PREVENTION STANDARDS
IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE

V I N 5 X Y K T 3 A 1 2 B G 1 4 7 6 5 3

MPV

NT

3

ps.
b.

002

A-1.

Vehicle's Certification Label



TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

SEATING CAPACITY NOMBRE DE PLACES	TOTAL 5	FRONT AVANT 2	REAR ARRIÈRE 3
--------------------------------------	---------	------------------	-------------------

The combined weight of occupants and cargo should never exceed 420 kg or 930 lbs.
 Le poids total des occupants et du chargement ne doit jamais dépasser 420 kg ou 930 lb.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS À FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
FRONT AVANT	P235/65R17	230kPa, 33psi	
REAR ARRIÈRE	P235/65R17	230kPa, 33psi	
SPARE DE SECOURS	T165/90R17	420kPa, 60psi	

002

J
FRONT
REAR

Vehicle's Tire Placard

A-3.



Pre-Test Front View of Vehicle

A-4.



Post-Test Front View of Vehicle

A-5.



Pre-Test Left Side View of Vehicle

A-6.



Post-Test Left Side View of Vehicle



Pre-Test Left Rear Close-up View of Vehicle

A-8.



Post-Test Left Rear Close-up View of Vehicle

A-9.



Pre-Test Right Side View of Vehicle

A-10.



Post-Test Right Side View of Vehicle



Pre-Test Right Rear Close-up View of Vehicle



Post-Test Right Rear Close-up View of Vehicle

A-13.



Pre-Test Rear View of Vehicle

A-14.



Post-Test Rear View of Vehicle

A-15.



Pre-Test ¼ Frontal View From Right Side of Vehicle



Post-Test $\frac{3}{4}$ Frontal View From Right Side of Vehicle



Pre-Test ¾ Rear View From Right Side of Vehicle



Post-Test ¾ Rear View From Right Side of Vehicle



Pre-Test 3/4 Rear View From Left Side of Vehicle



Post-Test ¾ Rear View From Left Side of Vehicle




A-21.

Pre-Test Impact Point




Post-Test Impact Point




A-23.

Pre-Test Underbody View 1




A-24.

Post-Test Underbody View 1




A-25.

Pre-Test Underbody View 2



Post-Test Underbody View 2

A-27.



Pre-Test Underbody View 3

A-28.



Post-Test Underbody View 3



A-29.

Pre-Test Front View of MDB

A-30.



Post-Test Front View of MDB



A-31.

Pre-Test $\frac{3}{4}$ Right Side View of MDB



Post-Test ¾ Right Side View of MDB

A-33.




Pre-Test $\frac{3}{4}$ Left Side View of MDB

A-34.



Post-Test $\frac{3}{4}$ Left Side View of MDB

A-35.




Pre-Test Top View of MDB

A-36.



Post-Test Top View of MDB

A-37.



Static Rollover at 90 Degrees

A-38.



Static Rollover at 180 Degrees



A-39.

Static Rollover at 270 Degrees



A-40.

Static Rollover at 360 Degrees